



(800) 899-0620

PersonalizedDoormats.com

Anti-Fatigue Logomat

SPECIFICATIONS

Anti-Fatigue Logomats feature your custom logo or artwork on a nitrile rubber surface while providing exceptional anti-fatigue properties.

- Photographic quality printing
- Features 150 standard color options
- Exceptional anti-fatigue properties
- Diamond surface pattern offers superior traction
- UV, chemical and oil resistant
- Easy to clean - hose off or sweep

SURFACE

Material: Nitrile rubber

Logo/Image Material: Polymeric film

CUSHION

Material: High-density, closed-cell nitrile/PVC-blended foam

OVERALL MAT THICKNESS: 5/8 inch (0.6250")

STANDARDS & TESTING

- Compression Deflection:
 - 47.8% at 20 psi
 - 61.6% at 40 psi
- Certified high-traction by the National Floor Safety Institute (NFSI)
- ASTM C1028-96 static coefficient of friction:
 - Dry 0.79
 - Wet 0.75
- Passes flammability standard DOC-FF1-70
- Melt point over 500 degrees F. Tested at temperatures up to 1800 degrees F for welding/slag resistance (specific results from test available upon request)

Please note, that due to the manufacturing process of Anti-Fatigue Logomats - shrinkage is expected. Rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



(800) 899-0620

PersonalizedDoormats.com

Design Specifications

A digital print on polymeric film allows customers to customize the Anti-fatigue mat with logos, images, and messages.

Minimum Text Height: 1/4"

Minimum Line Thickness: 1/16"

These text requirements are for general use; however, special fonts and very thin letter forms may need to be made larger or thicker and will be approached on a case-by-case basis.

White is prone to discolor and cannot be used as the background or any part of the imprint area. The product's color palette offers three light colors to use in place of White: F5, N9 and N10. The background color of the imprint area should not be set to these light colors. It is difficult to keep the logo clean through the manufacturing process.

**Please submit high quality logo/image files
to ensure the highest print quality and accurate color matching**

| Acceptable |
|-------------------------|
| Vector Graphic Files: |
| AI, EPS, PDF, CDR, SVG |
| Image Files: |
| TIFF (150-921 DPI/PPI)* |
| JPG (150-921 DPI/PPI)* |
| PNG (150-921 DPI/PPI)* |

*For carpeted mats, 150 to 300 DPI/PPI is required. For rubber mats, a minimum of 921 DPI/PPI is required.



price match 
guarantee
If the product is identical, we'll beat the price



(800) 899-0620

PersonalizedDoormats.com

Cleaning Instructions

Anti Fatigue mats can be cleaned by scrubbing with a deck brush (when needed), using detergent with a neutral pH, and rinsing with a hose or pressure washer. Mats should be laid flat or hung to dry.