



(800) 899-0620

PersonalizedDoormats.com

Rubber Backed Carpeted Standard Logomat

SPECIFICATIONS

Rubber Backed Carpeted Standard Logo Mats feature your custom logo or artwork digitally printed on eco-friendly PET fabric. Choose from 60 standard color options.

- Yarn contains 100% recycled content reclaimed from plastic
- State-of-the-art digital printing.
- Features 60 standard color options.
- Easy to clean - vacuum or steam clean.
- Stain resistant.

SURFACE

Material: PET (polyethylene terephthalate) printed/disperse-dyed yarn - contains 100% recycled content reclaimed from plastic

Weight: 23 ounces/yard²

Construction: Cut pile

Substrate: Freudenberg LUTRADUR® polyester spunbond non-woven fabric 3.8 oz. per square yard (130 grams per square meter)

BACKING

Material: Rubber (with 20% recycled content) - smooth or universal cleated

Thickness: 48-mil (body thickness 48-mil; border thickness 90-mil)

OVERALL MAT THICKNESS: 3/8 inch (0.375")

STANDARDS & TESTING

- Certified high-traction by the National Floor Safety Institute (NFSI)
- Passes flammability standard DOC FF1-70
- ESD rating of anti-static

Please note, that due to the manufacturing process of Rubber Backed Carpeted Standard Logomats - shrinkage is expected. Rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



(800) 899-0620

PersonalizedDoormats.com

Design Specifications

Rubber Backed Carpeted Standard logomats are produced using a layering process of color. Colors are matched to our standard pallet of 60 colors.

Minimum Text Height: 1" for serif fonts and 1/2" for sans serif fonts

Minimum Line Thickness: 1/8" except for white & light colors which should be at least 1/4"

These text requirements are for general use; however, special fonts and very thin letter forms may need to be made larger or thicker and will be approached on a case-by-case basis.

Light background colors should be avoided due to their tendency to show dirt on the mat more than a darker or neutral tone.

We also advise against the use of screens, tints, and transparencies in the design because they are not easily converted to our color palette.

**Please submit high quality logo/image files
to ensure the highest print quality and accurate color matching**

Acceptable
Vector Graphic Files:
AI, EPS, PDF, CDR, SVG
Image Files:
TIFF (150-921 DPI/PPI)*
JPG (150-921 DPI/PPI)*
PNG (150-921 DPI/PPI)*

*For carpeted mats, 150 to 300 DPI/PPI is required. For rubber mats, a minimum of 921 DPI/PPI is required.



price match 
guarantee
If the product is identical, we'll beat the price



(800) 899-0620

PersonalizedDoormats.com

Cleaning Instructions

Rubber Backed Carpeted Standard Logo mats can be cleaned in several different ways.

- They can be commercially laundered (see Laundering Instructions)
- Vacuumed regularly (daily in high-traffic areas; weekly in lower-traffic applications)
- Cleaned with an extractor, or hosed off as necessary to remove heavy soil.
- Hang to dry.

Mats should always be dry before they are placed back in service.

Laundering Instructions

Rubber Backed Carpeted Logomats that are backed with nitrile rubber can be commercially laundered. Proper laundering will prolong the life of the mat by preventing the buildup of soil and soap residue.

Rubber Backed Carpeted Logomats are manufactured using PET Yarn. PET is a type of polyester that needs to be processed using the proper chemistry to obtain optimal results. When PET products are exposed to oils, the yarn has an affinity to retain these oils. We would recommend starting with 2 oz. of detergent per cwt., and 1 oz. of alkali per cwt, and add 4-oz. of hydrogen peroxide. The level of chemicals required will depend on the type of accounts you service. Please consult with your chemical supplier if you have additional questions or concerns.

1. Flush 2-3 minutes, medium water level, 120 degrees F (49 degrees C)
2. Flush (optional) 2-3 minutes, medium water level, 120 degrees F (49 degrees C)
3. Break 5-10 minutes, high water level, 120 degrees F (49 degrees C)
4. Rinse 2 minutes, high water level, cold
5. Rinse 2 minutes, high water level, cold
6. Extract (low speed) 1-2 minutes
7. Shake out (rotate wheel at wash speed with drain open) 1 minute
8. Extract (high speed max - 250 Gs) 3-5 minutes
9. Dry 5-10 minutes, 180 degrees F (82 degrees C) basket temp.
10. Cool down 5 minutes
11. Lay mats flat following removal from washer or dryer. Allow to cool before rolling.

For heavy soil mats, increase temperature to max 140 degrees F (60 degrees C). Break should not exceed pH of 9.5; use low pH non-ionic detergents. Do not over-dry mats; basket temperature of dryer should not exceed 180 degrees F (82 degrees C). If mats are not dried, final rinse can be increased to 140 degrees F (60 degrees C). This will reduce moisture retention following extraction.