



(800) 899-0620

PersonalizedDoormats.com

Rubber Scraper Logomat

SPECIFICATIONS

Rubber Scraper Logo Mats feature a custom logo or artwork on a Rubber Scrape mat. Multi-colored images are printed on vinyl and heat pressed into a nitrile rubber surface.

- Photographic quality logos.
- Features 150 standard color options.
- Circular surface cleats for scraping and traction.
- Easy to clean - hose off or sweep.

CONSTRUCTION

Material: Rubber

Logo/Image Material: Polymeric film

Thickness: 3/16 inch (0.1875")

STANDARDS & TESTING

- **Certified high-traction by the National Floor Safety Institute (NFSI)**
- **Passes DOC-FF1-70 for surface flammability**
- **ASTM C1028-96 static coefficient of friction:**
 - Dry 0.86**
 - Wet 0.72**

Please note, that due to the manufacturing process of Rubber Scraper Logomats - shrinkage is expected. Rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



(800) 899-0620

PersonalizedDoormats.com

Design Specifications

A digital print on polymeric film allows customers to customize the Rubber Scraper mat with logos, images, and messages.

Minimum Text Height: 1/2" (includes lowercase text)

Minimum Line Thickness: 1/16"

These text requirements are for general use; however, special fonts and very thin letter forms may need to be made larger or thicker and will be approached on a case-by-case basis.

White is prone to discolor and cannot be used as the background or any part of the imprint area. The product's color palette offers three light colors to use in place of White: F5, N9 and N10. The background color of the imprint area should not be set to these light colors. It is difficult to keep the logo clean through the manufacturing process.

**Please submit high quality logo/image files
to ensure the highest print quality and accurate color matching**

Acceptable
Vector Graphic Files:
AI, EPS, PDF, CDR, SVG
Image Files:
TIFF (150-921 DPI/PPI)*
JPG (150-921 DPI/PPI)*
PNG (150-921 DPI/PPI)*

*For carpeted mats, 150 to 300 DPI/PPI is required. For rubber mats, a minimum of 921 DPI/PPI is required.



price match 
guarantee
If the product is identical, we'll beat the price



(800) 899-0620

PersonalizedDoormats.com

Cleaning Instructions

Rubber Scraper Logomats can be commercially laundered (see laundering instructions) or cleaned using the instructions below.

- Scrub with a deck brush (when needed) using detergent with a neutral pH.
- Rinse with a hose or pressure washer.
- Lay flat or hang to dry.

Laundering Instructions

Rubber Scraper Logomats that are nitrile rubber that can be commercially laundered. Proper laundering will prolong the life of the mat by preventing the buildup of dirt and residue. The level of chemicals required will depend on the type of accounts you service. Please consult with your chemical supplier if you have additional questions or concerns.