

### StrandShield Vinyl Loop Inlay

### **SPECIFICATIONS**

StrandShield is more than just a mat—it's a fully drainable outdoor matting solution engineered to provide superior dirt control, safety, and durability while also enhancing the aesthetic appeal of your facilities.

- All weather indoor / outdoor
- Fully drainable looped vinyl with superior dirt and moisture control
- · Inlaid design with rubber edging
- UV & water resistant
- Designed to withstand heavy foot traffic and maintain long term appearance.
- Minimal shrinking during Manufacturing
- 7 standard color options available at this time
- No setup fees, no minimums

#### CONSTRUCTION

Mat Material: Vinyl

**Edging:** Vinyl ADA compliant reducer edging.

**Logo/Image Material:** Inlaid Vinyl **Backing:** None - Fully drainable

**OVERALL MAT THICKNESS:** Approximately 1/4 inch

Mat sizes are available up to  $4' \times 60'$ . We can make larger mats but seams can be visible. We can suggest to keep mats to 8' wide or less thereby having only one field seam.

#### **Turnaround time:**

10-15 business days plus 2-5 additional business days for delivery from Georgia after the order is placed.



(800) 899-0620 PersonalizedDoormats.com

## **Design Specifications**

Strandshield Vinyl Loop logo mats are produced from flexible, extruded vinyl or PVC strands that are looped together in a random coil or "spaghetti" design. The custom designs are made using an inlay process, where colored material is cut out from different color vinyl pieces and assembled like a puzzle with special glue.

As a result, there are very strict design requirements for this product. White material should not be used as the background color or for large sections of the mat as it is difficult to keep the color clean.

Minimum Text Height: 3" (includes lower case text)

Minimum Line Thickness: 3/8"

Any space between letters or design elements must be at minimum 3/8" The text requirements are for general use; however, special fonts and very thin letter forms may need to be made larger or thicker and will be approached on a case-by-case basis. Gradients, tints, screens and transparencies are not supported and can not be used.

# Please submit high quality logo/image files to ensure the highest print quality and accurate color matching

Acceptable	
Vector Graphic Files:	
AI, EPS, PDF, CDR, SVG	
Image Files:	
TIFF (150-921 DPI/PPI)*	
JPG (150-921 DPI/PPI)*	
PNG (150-921 DPI/PPI)*	

\*For carpeted mats, 150 to 300 DPI/PPI is required. For rubber mats, a minimum of 921 DPI/PPI is required.





## **Cleaning Insructions**

Strandshield Logo mats can be cleaned by vacuuming, using detergent with a neutral pH, brushing areas of concern with a soft brush, and/or rinsing with a hose.