



(800) 899-0620

PersonalizedDoormats.com

Waterhog Inlay Logomat

SPECIFICATIONS

WaterHog Inlay mats feature your custom logo or artwork inlaid on a polyester fabric where the surface can scrape and/or dry your feet while being able to withstand extremely high traffic.

- Logo pieces are hand-assembled and inlaid
- Features 19 standard color options
- Bi-level surface scrapes and traps dirt and moisture
- Water dam border holds up to 1.5 gallons of water per square
- Durable, UV resistant
- Hybrid mat - great for scraping & drying shoes
- Easy to clean - vacuum or hose off

SURFACE

Fiber: 97% Solution-dyed polypropylene, 3% latex

Weight: 24 ounces/yard²

Construction: Needle-punched

Design: Squares

BACKING

Material: Rubber - smooth or universal cleated

Thickness: 78-mil (body thickness 78-mil; border thickness 143-mil)

OVERALL MAT THICKNESS: 3/8 inch (0.3750")

STANDARDS & TESTING

- Certified high-traction by the National Floor Safety Institute (NFSI)
- Passes CPSC FF 1-70 for the surface flammability of carpets

Please note, that due to the manufacturing process of Waterhog Inlay Logomats - shrinkage is expected. Rubber shrinks and expands in conjunction with temperature and time. Tolerable manufacturing size variance is 3-5%.



(800) 899-0620

PersonalizedDoormats.com

Design Specifications

WaterHog Inlay mats are produced using an inlay process, where colored material is cut and pieced together by hand before pressing into rubber. As a result, there are very strict design requirements for this product. PMS color matching is not available. White material should not be used as the background color or for large sections of the mat as it is difficult to keep the color clean.

Minimum Text Height: 3" (includes lower case text)

Minimum Line Thickness: 3/8"

Any space between letters or design elements must be at minimum 3/8"

The text requirements are for general use; however, special fonts and very thin letter forms may need to be made larger or thicker and will be approached on a case-by-case basis.

Gradients, tints, screens and transparencies are not supported and should not be used.

**Please submit high quality logo/image files
to ensure the highest print quality and accurate color matching**

Acceptable
Vector Graphic Files:
AI, EPS, PDF, CDR, SVG
Image Files:
TIFF (150-921 DPI/PPI)*
JPG (150-921 DPI/PPI)*
PNG (150-921 DPI/PPI)*

*For carpeted mats, 150 to 300 DPI/PPI is required. For rubber mats, a minimum of 921 DPI/PPI is required.



price match 
guarantee
If the product is identical, we'll beat the price



(800) 899-0620

PersonalizedDoormats.com

Cleaning Instructions

For the best results, utilize the following cleaning method to clean your WaterHog Inlay mat:

- Vacuum regularly (daily in high-traffic commercial areas; weekly in lower traffic areas).
- Extract clean to remove heavy soil/debris.
- Hang mat to dry.

Always make sure the mat is dry before placing it back in service.